

UPS 650 VA INTERACTIVE WALL

AX-650IM

INPUT

Voltage	100 V 110 V 120 V: 80 ~ 150 Vac; 220 V 230 V 240 V: 162 ~ 295 Vac (220 V: 145 ~ 295 Vac optional)
Frequency	50 / 60 Hz ± 10% (auto-sense)

OUTPUT

Voltage	100 V 110 V 120 Vac ± 10% or 220 V 230 V 240 Vac ± 10%
Frequency	50 / 60 Hz ± 1% (auto-sense)
Waveform	Mains mode Pure sine wave Battery mode Simulated sine wave
Transfer time	Typical 2 ~ 7 ms; Max.10 ms

BATTERIES

DC voltage	12 V
Configuration	12 V / 7.0 Ah × 1
Recharge time	6 ~ 8 h

COMMUNICATIONS

USB / RS232 / SNMP (optional)	Supports Windows® 98 / 2000 / 2003 / XP / Vista / 2008 / 7 / 8 / 10
-------------------------------	---

OTHERS

Protections	Short circuit - battery overcharge – overdischarge – overload - surge
Humidity	20 ~ 90% RH @ 0 ~ 40°C (non-condensing)
Noise level	≤ 45 dB (1 m)
Net / Gross weight (kg)	4.5 / 5.0
Dimensions (W × D × H)	185 × 280 × 95 (mm)
Packaged dimensions (W×D×H)	145 × 333 × 238 (mm)
Quantity / 20 ft	2400 pcs



*All specifications subject to change without notice.

*Custom-made specifications are acceptable.