

2-way Tap 2.4G



Features :

- Passive transmission device
- Applicable to 5-2400MHz ,IN-OUT POWER PASS
- Full SMT technique Low insertion loss
- High isolation between ports
- Zinc alloy tinning shell ,Connectors: "F" type female, 75ohm.

TECH SPECIFICATION

2 way Tap							
Item		Parameters					
Tap Loss (dB)	Normal	08	12	14	16	20	25
Insertion Loss IN-OUT (dB)	5-470MHz	≤4.5	≤3.5	≤2.2	≤1.8	≤1.8	≤1.8
	470-750MHz	≤4.8	≤3.5	≤2.4	≤1.7	≤1.7	≤1.7
	750-1002MHz	≤4.8	≤3.7	≤2.6	≤2.2	≤2.2	≤2.2
	1002-1675MHz	≤5.2	≤4.0	≤3.2	≤2.6	≤2.6	≤2.6
	1675-2400MHz	≤5.8	≤4.5	≤3.6	≤3.0	≤3.0	≤3.0
Reverse Isolation OUT-TAP (dB)	5-470MHz	≥18	≥18	≥18	≥18	≥18	≥18
	470-750MHz	≥20	≥20	≥20	≥20	≥20	≥20
	750-1002MHz	≥20	≥20	≥20	≥20	≥20	≥20
	1002-1675MHz	≥20	≥20	≥20	≥20	≥20	≥20
	1675-2400MHz	≥20	≥20	≥20	≥20	≥20	≥20
Tap-Tap Isolation (dB)	5-470MHz	≥18	≥18	≥18	≥18	≥18	≥18
	470-750MHz	≥18	≥18	≥18	≥18	≥18	≥18
	750-1002MHz	≥18	≥18	≥18	≥18	≥18	≥18
	1002-1675MHz	≥16	≥16	≥16	≥16	≥16	≥16
	1675-2400MHz	≥16	≥16	≥16	≥16	≥16	≥16