

TV-SATELLITAL TAPS 2.4GHZ

The bdn Taps are designed to comply with the highest current standards for Analog and Digital TV/SAT technologies. BDN taps are manufactured with a shielded zamak chassis for greater protection from electromagnetic interference, ideal for community TV projects, television networks in hotels, hospitals and shopping centers.

TECH SPECIFICATION

Description	INDOOR 2.4GHz TAP 6-WAY				
Item	Tap Value	16	20	25	27
Tap loss (IN-TAP)		±1.5dB	±1.5dB		±1.5dB
Insertion Loss (IN-OUT)		-dB Max			
5-47MHz		4,5	3	3	2,5
47-1000MHz		4,5	3	3	2,5
1000-1750MHz		5,5	4	3,6	3,1
1750-2150MHz		5,5	4	3,6	3,1
2150-2400MHz		6	5	4,5	5
Insolation (TAP-TAP)		-dB Min			
5-47MHz		20	20	20	20
47-1000MHz		20	20	20	20
1000-1750MHz		20	20	20	20
1750-2150MHz		20	20	20	20
2150-2400MHz		20	20	20	20
Insolation (TAP-OUT)		-dB Min			
5-47MHz		20	20	20	20
47-1000MHz		20	20	20	20
1000-1750MHz		20	20	20	20
1750-2150MHz		20	20	20	20
2150-2400MHz		20	20	20	20
Return Loss (IN, OUT, TAP)		-dB Min			
5-47MHz		15	15	15	15
47-1000MHz		15	15	15	15
1000-1750MHz		15	15	15	15
1750-2150MHz		15	15	15	15
2150-2400MHz		15	15	15	15
DC PASS		IN <- -> OUT 24V 500mA			