

TV-SATELLITAL TAPS 2.4GHZ

The bdn Taps are designed to comply with the highest current standards for Analog and Digital TV/SAT technologies. BDN taps are manufactured with a shielded zamak chassis for greater protection from electromagnetic interference, ideal for community TV projects, television networks in hotels, hospitals and shopping centers.

TECH SPECIFICATION

Description	INDOOR 2.4GHz TAP 8-WAY			
Item \ Tap Value	16	18	20	25
Tap loss (IN-TAP)	±2dB	±1.5dB		
Insertion Loss (IN-OUT)	-dB Max			
5-47MHz	4,5	4,2	3	3
47-1000MHz	4,5	4,2	3	3
1000-1750MHz	5,5	5,2	4	3,6
1750-2150MHz	5,5	5,2	4	3,6
2150-2400MHz	6	5,8	5	4,5
Insolation (TAP-TAP)	-dB Min			
5-47MHz	20	20	20	20
47-1000MHz	20	20	20	20
1000-1750MHz	20	20	20	20
1750-2150MHz	20	20	20	20
2150-2400MHz	20	20	20	20
Insolation (TAP-OUT)	-dB Min			
5-47MHz	20	20	20	20
47-1000MHz	20	20	20	20
1000-1750MHz	20	20	20	20
1750-2150MHz	20	20	20	20
2150-2400MHz	20	20	20	20
Return Loss (IN, OUT, TAP)	-dB Min			
5-47MHz	15	15	15	15
47-1000MHz	15	15	15	15
1000-1750MHz	15	15	15	15
1750-2150MHz	15	15	15	15
2150-2400MHz	15	15	15	15
DC PASS	IN ← → OUT 24V 500mA			

