


DHI-ASGG100T

Dahua Tripod Turnstile(No hole,Outdoor)-DHI-ASGG100T



Scene

Suitable for access control of entrances and exits in compound buildings, manufacturing workshop, tourist attraction, construction site and more.

Technical Specification

System	
Main Processor	Embedded Processor
Basic	
Product Type	Tripod Turnstile
Status Indicator Light	Solid red: Bi-directional authorization mode; Solid green: Bi-directional free mode or Unidirectional free mode; Green arrow flashing: Authorization was successful.
Main Materials of Cabinet	SUS304
Surface Treatment	Stainless Steel Ink Etching
Performance	
MCBF	3000000
Passage Width	600 mm (1.97")
Passing Speed	20–30 person/min
Top Cover Thickness	1.2 mm (0.05")
Frame Thickness	0.8 mm (0.03")
Barrier Material	Stainless steel
Number of Face Module Installation Holes	0
Number of Access Controllers	0

- 304 stainless steel cabinet with a thickness of 0.8 mm.
- The arm automatically falls during a fire and power failure. (When the arm falls, the turnstile arm must be pushed down and then lifted up again).
- MCBF (Mean Cycles between Failures) is no less than 3 million times.
- Mechanical anti-tailing.
- Supports configuring the passing time for people.
- Restores the system settings to their default values.
- Memorizes passing data for entry and exit.
- Features 9 modes for entry and exit including controlled, prohibited, and free. Combine these modes for more options.
- Supports being connected to multiple types of modules such as face, fingerprint and QR code. Combine these modules for more options.

Port

Fire Port	1
-----------	---

General

Power Supply	100–240 VAC, 1.5 A
Protection	IPX4
Power Consumption	≤10 W (standby), ≤40 W (working)
Product Dimensions	1,200 mm × 220 mm × 980 mm (47.24" × 8.66" × 38.58") (L × W × H)
Packaging Dimensions	1,288 mm × 361 mm × 1,055 mm (50.71" × 14.21" × 41.54") (L × W × H)
Gross Weight	23.7 kg (52.25 lb)
Operating Temperature	–25 °C to +70 °C (–13 °F to +158 °F)
Operating Humidity	5%–95% (RH), non-condensing
Operating Environment	Indoor; Outdoor
Storage Temperature	0 °C to +40 °C (+32 °F to +104 °F)
Storage Humidity	30%–75%

Ordering Information

Type	Model	Description
Tripod Turnstile	DHI-ASGG100T	Dahua Tripod Turnstile(No hole,Outdoor)-DHI-ASGG100T

Dimensions (mm[inch])

